



## Epson SureColor SC-S60600

- Produce durable outdoor signs and banners, window and back-lit displays, wallpaper and decor, vehicle wraps and POS, labels and more... AT HIGH SPEED
- Compatible with coated and uncoated paper, vinyl, canvas, film, mesh, and synthetic stocks
- Superior imaging with low grain, enhanced gamut, contrast and gloss levels
- Supports tiling applications with exceptional colour precision, consistency and print linearity
- Low running cost with rapid job set-up, minimum maintenance, low power & ink consumption
- Easy to operate with a see-through platen cover, remote management & status notification
- Extremely fast job completion with easy media set-up, integrated auto take-up and air dryer
- Enhanced reliability with a self cleaning printhead, headguard, and air filtration system
- Suits installation in factory, shop and air-conditioned studio environments
- High durability with flexible cover extendable up to FIVE YEARS
- Ships complete with NEW Epson Edge Print Software

## **Epson SureColor SC-S60600**

## **Product Specifications** PRINTING TECHNOLOGY Self-cleaning DUAL PrecisionCore™ TFP with VSDT Print Engine Epson Precision Dot Technology Integrated headguard Media Handling Auto media setting, auto skew correction, advanced auto tension control (Ad-ATC) & auto take-up (ATU), Print drying system INCLUDED **Print Quality** 1440 x 1440 dpi max res, 4.2 pl min drop size **INK SYSTEM** Type Epson UltraChrome® GS3 Eco-Solvent Colour Set DUAL CMYK 8 x 700 ml cartridge Loading PRINT SPEEDS<sup>1</sup> 95.3 m<sup>2</sup>/h Draft Billboard 52.3 m<sup>2</sup>/h Ranner 29.4 m<sup>2</sup>/h Vinyl, Canvas & Paper 17.6 m<sup>2</sup>/h Film (Front & Backlit) 6.8 m<sup>2</sup>/h **MEDIA HANDLING** 300-1626 mm (64") wide, 1 mm max thickness Sizing Input Single roll, 45 kg max weight, 250 mm max diameter Output Sheet (manual cut) or roll (200 mm max diameter) Drying Individually adjustable input, platen & output heaters MANAGEMENT See-through platen with LED lighting **Features** On-board 2.7" Colour LCD panel Remote e-mail status & error reporting Ships with Epson Edge Print & Dashboard software. Compatible with a wide range of 3rd party RIP and workflow applications.



The **included** print drying system integrates with the printer to enable production at high speed and with heavy ink loads





The auto head cleaning & air filtration systems work in conjunction with the headguard to ensure superior reliability with reduced maintenance

## Better Products for a Better Future

Epson, SureColor, UltraChrome, PrecisionCore are registered trademarks of Seiko Epson Corporation. All other names and logos herein are for identification purpose only and are trademarks of their respective owners; Epson disclaims any and all rights. All print samples shown herein are simulations. Specifications are subject to change without notice; customers should review material posted on the web sites listed below for the latest information.

V4.0 November 2018

INTEGRATION	
INTEGRATION	0.0 0.7 4.7 44 0.10
Space Requirements	3.6 x 2.7 x 1.7 m (WxDxH)
Operational Temp	15 to 35°C (20 to 32°C recommended)
Operational Humidity	20 to 80% (40 to 60% recommended)
Power Requirement	3 x 240 V, 50/60 Hz, 5 A
Power Consumption	745 W operating/ 13 W sleep
Operational Noise	60.5 dB
Connectivity	USB2.0, 100BASE-TX/1000BASE-T
OPTIONS	
1YWSCS60600	1 Yr CoverPlus On-Site Service Extension
2YWSCS60600	2 Yr CoverPlus On-Site Service Extension
CONSUMABLES	
C13T724100	Maintenance cleaning kit
C135210044	Maintenance parts kit
C13T699300	Ink cleaner
C13T833192	700 ml black ink cartridge
C13T833292	700 ml cyan ink cartridge
C13T833392	700 ml magenta ink cartridge
C13T833492	700 ml yellow ink cartridge
C13T833092	Cleaning cartridge
C13T835192~492	700 ml KCMY 3M <sup>TM</sup> MCS <sup>TM</sup> ink cartridges <sup>2</sup>
CONFIGURATION OPTIONS	700 mi Rown Sivi Woo link cartilages
SCS606001YR	Printer with 1 Yr On-site Warranty
SCS606003YR	Printer with 1 Yr Wty & 2 Yr On-site CoverPlus
SCS606005YR	Printer with 1 Yr Wty & 2 x 2 Yr On-site CoverPlus

<sup>&</sup>lt;sup>1</sup> Figures are maximum engine speeds only. They do not include provisions for image processing, transfer, drying or post production. Nominated speeds may not be suitable for all media types and/or applications. Alternate print modes may be employed by RIP s/w for different results.
<sup>2</sup> For details on the MCS program including coverage, certification, terms & conditions please contact your local 3M office.



The Ad-ATC and ATU enable roll-to-roll production with superior linearity, parallelism, and tension for off-line processing and tiling applications







The printer can be managed through the control panel or via Epson Edge Dashboard complete with downloadable print & media profiles, remote e-mail status & error notifications. New Epson Edge Print software enables output of PS, EPS, Tiff, Jpeg, PNG & PDF files with image crop, layout & colour adjustment.





